

EZ iMarquee - 2 Lines 40 Characters

2 Lines 40 Characters - NEMA 12

The 2 Line 40 Char EZ iMarquee can hold up to a maximum of 40 characters (2") per line and features 2 lines of Tri-Color LEDs. EZ iMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity. All 2 Line 40 Character models are capable of communicating over RS232, RS422/485 and Ethernet. This is a Master and Slave LED Message Display with built-in PLC protocols and data logger.

2 Lines 40 Characters feature:

- 2 lines of 40 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

Characteristics:

Character Height: 2" / 4"
 Characters per Line: 40 / 20
 Number of Lines: 2 / 1
 Visibility: 100' / 200'

iMarquee features:

- Built-in PLC Protocols to Major Brand PLCs
- Store messages locally on the EZ iMarquee
- No PLC Ladder Logic Changes required to display plant / machine messages or alerts
- Datalogging Built-in
- Webserver with Remote Access
- Built-in Message Database
- Built-in Alarm Database
- Advanced Scripting/Logic within the Marquee Display itself



Model Number	Interface
EZiMT-2L40C	RS232, RS422/485 and Ethernet included

2 Lines 40 Characters Dimensions

