

## EZMarquee - 1 Line 40 Characters

### 1 Line 40 Characters - NEMA 4X

The 1 Line 40 Char EZMarquee can hold up to a maximum of 40 characters (2") per line and features 1 line of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 4X extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity. All 1 Line 40 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

### Characteristics:

Character Height:	2"
Characters per Line:	40
Number of Lines:	1
Visibility:	100'

### 1 Line 40 Characters feature:

- 1 line of 40 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 4X Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below



RED Outdoor

Model Number	Interface
<b>EZMR-1L40C-OUT</b>	RS232 and RS422/485 only
<b>EZMR-1L40C-E-OUT</b>	Ethernet included
<b>EZMR-1L40C-D-OUT</b>	DeviceNet included
<b>EZMR-1L40C-P-OUT</b>	Profibus included

RED Outdoor Highbright

Model Number	Interface
<b>EZMRH-1L40C-OUT</b>	RS232 and RS422/485 only
<b>EZMRH-1L40C-E-OUT</b>	Ethernet included
<b>EZMRH-1L40C-D-OUT</b>	DeviceNet included
<b>EZMRH-1L40C-P-OUT</b>	Profibus included



TRI color Outdoor

Model Number	Interface
<b>EZMT-1L40C-OUT</b>	RS232 and RS422/485 only
<b>EZMT-1L40C-E-OUT</b>	Ethernet included
<b>EZMT-1L40C-D-OUT</b>	DeviceNet included
<b>EZMT-1L40C-P-OUT</b>	Profibus included

### 1 Line 40 Characters

