

## EZMarquee - 2 Lines 10 Characters

### 2 Lines 10 Characters - NEMA 12

The 2 Line 10 Char EZMarquee can hold up to a maximum of 10 characters (2") per line and features 2 lines of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity. All 2 Line 10 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

### Characteristics:

Character Height: 2" / 4"  
 Characters per Line: 10 / 5  
 Number of Lines: 2 / 1  
 Visibility: 100' / 200'

### 2 Lines 10 Characters features:

- 2 lines of 10 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below.



Red Indoor

Model Number	Description
EZMR-2L10C	RS232 and RS422/485 Only
EZMR-2L10C-E	Ethernet Included
EZMR-2L10C-D	Devicenet Included
EZMR-2L10C-P	Profibus Included



Tri Color Indoor

Model Number	Description
EZMT-2L10C	RS232 and RS422/485 Only
EZMT-2L10C-E	Ethernet Included
EZMT-2L10C-D	Devicenet Included
EZMT-2L10C-P	Profibus Included

RED Outdoor Highbright

Model Number	Description
EZMRH-2L10C	RS232 and RS422/485 Only
EZMRH-2L10C-E	Ethernet Included
EZMRH-2L10C-D	Devicenet Included
EZMRH-2L10C-P	Profibus Included

