

EZMarquee - 4 Lines 40 Characters (Indoor)

4 Lines 40 Characters - NEMA 12

The 4 Line 40 Char EZMarquee can hold up to a maximum of 40 characters (2") per line and features 4 lines of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity.

All 4 Line 40 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

Characteristics:

Character Height: 2" / 4" / 6" / 8"
 Characters per Line: 40 / 20 / 13 / 10
 Number of Lines: 4 / 2 / 1 / 1
 Visibility: 100' / 200' / 300' / 400'

4 Lines 40 Characters feature:

- 4 lines of 40 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below



RED Indoor

TRI color Indoor

Model Number	Interface
EZMR-4L40C	RS232 and RS422/485 only
EZMR-4L40C-E	Ethernet included
EZMR-4L40C-D	DeviceNet included
EZMR-4L40C-P	Profibus included

Model Number	Interface
EZMT-4L40C	RS232 and RS422/485 only
EZMT-4L40C-E	Ethernet included
EZMT-4L40C-D	DeviceNet included
EZMT-4L40C-P	Profibus included

RED High-bright

(TOP)

(BOTTOM)

Model Number	Interface
EZMRH-4L40C	RS232 and RS422/485 only
EZMRH-4L40C-E	Ethernet included
EZMRH-4L40C-D	DeviceNet included
EZMRH-4L40C-P	Profibus included

(TOP)

4 Lines 40 Characters Dimensions

