


EZMarquee - 1 Line 20 Characters (Outdoor Sunlight)



1 Line 20 Characters - NEMA 4X

The 1 Line 20 Char EZMarquee can hold up to a maximum of 20 characters (2") per line and features 1 line of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 4X extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity. All 1 Line 20 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

Characteristics:

Character Height: 2"
 Characters per Line: 20
 Number of Lines: 1
 Visibility: 100'

1 Line 20 Characters feature:

- 1 line of 10 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below



RED Outdoor

RED Outdoor Highbright

| Model Number | Interface |
|--------------------------|--------------------------|
| EZMRH-1L20C-OUT | RS232 and RS422/485 only |
| EZMRH-1L20C-E-OUT | Ethernet included |
| EZMRH-1L20C-D-OUT | DeviceNet included |
| EZMRH-1L20C-P-OUT | Profibus included |

1 Line 20 Characters Dimensions

