

EZMarquee - 1 Line 40 Characters (Indoor Sunlight)

1 Line 40 Characters - NEMA 12

The 1 Line 40 Char EZMarquee can hold up to a maximum of 40 characters (2") per line and features 1 line of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity.


All 1 Line 40 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

Characteristics:


Character Height:	2"
Characters per Line:	40
Number of Lines:	1
Visibility:	100'

1 Line 40 Characters feature:

- 1 line of 40 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life



See the different communication interface options available in the charts below



RED Indoor

RED High-bright

Model Number	Interface
EZMRH-1L40C	RS232 and RS422/485 only
EZMRH-1L40C-E	Ethernet included
EZMRH-1L40C-D	DeviceNet included
EZMRH-1L40C-P	Profibus included

1 Line 40 Characters Dimensions

