

## EZMarquee - 2 Lines 40 Characters (Indoor Sunlight)

### 2 Lines 40 Characters - NEMA 12

The 2 Line 40 Char EZMarquee can hold up to a maximum of 40 characters (2") per line and features 2 lines of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity.


All 2 Line 40 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

### Characteristics:

Character Height: 2" / 4"  
 Characters per Line: 40 / 20  
 Number of Lines: 2 / 1  
 Visibility: 100' / 200'

### 2 Lines 40 Characters feature:

- 2 lines of 40 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life



See the different communication interface options available in the charts below



RED Indoor

### RED High-bright

Model Number	Interface
<b>EZMRH-2L40C</b>	RS232 and RS422/485 only
<b>EZMRH-2L40C-E</b>	Ethernet included
<b>EZMRH-2L40C-D</b>	DeviceNet included
<b>EZMRH-2L40C-P</b>	Profibus included

### 2 Lines 40 Characters Dimensions

