


## EZMarquee - 4 Lines 20 Characters (Outdoor Sunlight)



### 4 Lines 20 Characters - NEMA 4X

The 4 Line 20 Char EZMarquee can hold up to a maximum of 20 characters (2") per line and features 4 lines of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 4X extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity. All 4 Line 20 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

### Characteristics:

Character Height: 2" / 4" / 6" / 8"  
 Characters per Line: 20 / 10 / 6 / 5  
 Number of Lines: 4 / 2 / 1 / 1  
 Visibility: 100'/200'/300'/400'

### 4 Lines 20 Characters feature:

- 4 lines of 20 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below



RED Outdoor

RED Outdoor Highbright

Model Number	Interface
<i>EZMR-H4L20C-OUT</i>	RS232 and RS422/485 only
<i>EZMRH-4L20C-E-OUT</i>	Ethernet included
<i>EZMRH-4L20C-D-OUT</i>	DeviceNet included
<i>EZMRH-4L20C-P-OUT</i>	Profibus included

### 4 Lines 20 Characters Dimensions

