

EZMarquee - 4 Lines 20 Characters (Indoor Sunlight)

4 Lines 20 Characters - NEMA 12


The 4 Line 20 Char EZMarquee can hold up to a maximum of 20 characters (2") per line and features 4 lines of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 12 extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity. All 4 Line 20 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

Characteristics:

Character Height:	2" / 4" / 6" / 8"
Characters per Line:	20 / 10 / 6 / 5
Number of Lines:	4 / 2 / 1 / 1
Visibility:	100'/200'/300'/400'

4 Lines 20 Characters feature:

- 4 lines of 20 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- Hang Mounting
- NEMA 12 Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life



See the different communication interface options available in the charts below



RED Indoor

RED High-bright

Model Number	Interface
EZMRH-4L20C	RS232 and RS422/485 only
EZMRH-4L20C-E	Ethernet included
EZMRH-4L20C-D	DeviceNet included
EZMRH-4L20C-P	Profibus included

4 Lines 20 Characters Dimensions

